



Tablecloth Underlay Instruction Manual

Product Note

You have purchased a high-quality tablecloth underlay for smooth surfaces. It prevents the tablecloth from slipping and protects the table surface from pressure marks, scratches and liquids. It also reduces the background noise when setting and covering the crockery. In order to enjoy the tablecloth for a long time and to protect warranty claims, please observe the following information.

Security

The tablecloth underlay may only be used on dry and clean table surfaces. It must not be placed on table tops sealed with nitrocellulose lacquer without hardness additive or with water-based lacquer. Avoid direct contact with hot pots and pans, as well as with open flames or heat sources.

Preparation

Lay out the tablecloth underlay and leave it flat for 24 hours, if necessary, so that it can fully unfold. Then clean the tabletop and allow it to dry thoroughly. Lay the underlay with the embossed side facing down. If necessary, cut along the edge of the table with scissors. To protect the edge of the table, allow the underlay to protrude by 10 cm. Smooth out any creases or waves from the center outwards.

Care instructions

The tablecloth underlay can simply be wiped with a damp cloth. In heavily soiled, it can be washed in the washing machine at up to 60 °C. Do not use fabric softener and do not put the underlay in the tumble dryer.

Composition

Polyester glass yarn fabric, coated on both sides with special PVC paste.

A. Kolckmann GmbH

Obere Schlosstr. 14073553 Alfdorf

www.kolckmann.de

ako@kolckmann.de

Created on: 04.08.2025