



Instructions for use of carpet underlays on textile and smooth floors

Product Note

You have purchased a high-quality carpet underlay. This is used to hold loose carpets in place on textile and smooth floors to prevent them from slipping or rippling. In order to enjoy it for a long time and to protect any warranty claims, please observe the following information. With this carpet underlay, you can lay your carpet or runner on textile and smooth floors such as carpet, laminate, parquet, vinyl, PVC, stone and tiled floors. The underlay is suitable for underfloor heating.

Security

The carpet underlay may only be used on dry and clean floors. It must not be laid out on freshly oiled, waxed or damp floors. In the case of lacquer sealers, we recommend that the underlay is only laid out after the swaler has cured for at least three months. Avoid contact with naked flames or heat sources.

Preparation

Clean the floor surface and allow it dry thoroughly. If necessary, use scissors to cut the underlay approx. 2-5 cm smaller than the carpet. Lay out the carpet underlay and, if necessary, leave it flat for 24 hours to allow it to unfold completely. Smooth out any creases or waves from the center outwards.

Care instructions

The carpet underlay can be washed in the washing machine up to 30°C. Do not use fabric softener or put the pad in the dryer.

Composition

100% polyester fibers, needled and sprayed with acrylate-based adhesive.

A. Kolckmann GmbH

Obere Schlosstr. 14073553 Alfdorf

www.kolckmann.de

ako@kolckmann.de

Created on: 04.08.2025