



Instructions for use of carpet underlays on smooth floors

Product Note

You have purchased a high-quality carpet underlay. It is used to fix loose carpets to smooth floors and thus prevent slipping or wave formation. In order to enjoy it for a long time and to protect any warranty claims, please note the following information. With this carpet underlay, you can fix your carpet or runner on smooth floors such as laminate, parquet, vinyl, PVC, stone and tile floors. The underlay is suitable for underfloor heating.

Security

The carpet underlay must only be used on dry and clean floors. It is only suitable for solvent-free oil and wax sealants. In the case of parquet or stone floors sealed manually or on site, it is essential to follow the recommendations of the sealer manufacturer. This is because certain types of sealants can cause reactions with the underlay. If this is the case, use AKO TOPVLIES or AKO PRIMA. In any case, observe a curing time of three months for new seals. Avoid contact with open flames or heat sources.

Preparation

Clean the floor surface and let it dry well. If necessary, cut the underlay with scissors about 2-5 cm smaller than the carpet on top. Lay out the carpet underlay and, if necessary, leave it flat for 24 hours so that it fully unfolds. Smooth out any wrinkles or waves from the center outwards.

Care instructions

The carpet underlay can be easily wiped clean with a damp cloth. In the case of heavy soiling, it can be washed in the washing machine up to 60 °C. Do not use fabric softener or put the pad in the dryer.

Composition

Polyester glass yarn fabric, coated on both sides with special PVC paste.

A. Kolckmann GmbH

Obere Schlossstr. 140

73553 Alfdorf

www.kolckmann.de

ako@kolckmann.de

Created on: 01.09.2025